

VX-2200-DO-10

VHF/UHF Mobile Radios

SPECIFICATION SHEET

Wide Band Coverage and High-Power Performance

With 10W VHF / 10W UHF power output for effective communications transmission, the VX-2200-DO-10 provides reliability, extensive signaling features and enhanced channel capacity for maximum return on your investment. Die-cast aluminum construction helps dissipate heat and absorbs vibration for durability.

Expanded Frequency Options for Greater Coverage

Designed to cover the full band in the VHF and upper range of the UHF bands, get wide band coverage in one radio.

Broad Channel Capacity

Get 8 channels for easy operation with the VX-2100 Series or 128 channels for large group communications in the VX-2200-DO-10 to get the job done.

More Scanning Options

Compared to other mobile two-way radios in its class, the VX-2200-DO-10 Series provides exceptional flexibility in scanning features that is designed to optimise operation for a wide variety of environments. In addition to basic scan, you also get Priority, Dual Watch, Follow-me, Follow-me Dual Watch and Talk Around scanning built-in.

When Safety Counts

The VX-2200-DO-10 Series comes standard with built-in Emergency alert for enhanced driver safety. A panic button can be triggered by the front panel button to alert the dispatcher when problems arise.

Easily Integrate with Existing MDC System

Add the optional VME-100 board to make VX-2200-DO-10 mobile radios compatible for use with the rest of your MDC-1200® fleet.

Exclusive Auto-Range Transpond System – ARTS™

Only Vertex Standard radios are designed to inform you when you and another ARTS™-equipped station are within communication range. If out of range for more than 2 minutes, your radio senses no signal has been received and beeps to alert you. The base station can then alert the field unit to move back in range. A great solution to keep your workers co-ordinated.



VX-2200-DO-10

The Vertex Standard Difference

Our number one goal is achieving superior customer satisfaction by delivering products and services that exceed your expectations. Count on Vertex Standard for radios that are built to last and designed to provide more features for a better return on your investment. Ask your Dealer for more details.

Additional Features

- Four programmable keys
- 8-Character alphanumeric display (VX-2200-DO-10)
- 1-Character numeric display (VX-2100)
- RSSI signal strength indicator
- 2-Tone encode and decode
- 5-Tone signaling
- CTCSS / DCS Encode and Decode
- DTMF Paging
- Stun / kill / revive (5-tone)
- Remote listen
- Lone Worker
- D-Sub 15 Pin accessory connector
- Public address / horn alert
- Radio-to-radio cloning

Accessories

- MH-25A8J: Standard microphone

VX-2200-DO-10 Specifications

	VHF	UHF
General Specification		
Frequency Range	134 – 174 MHz	400 - 470 MHz, 450 - 520 MHz
Number of Channels and Groups	128 and 8 Groups (VX-2200-DO+10) 8 and 1 Groups (VX-2100)	
Power Supply Voltage	13.6V DC ± 15%	
Channel Spacing	12.5 / 20 / 25 kHz	
PLL Steps	2.5 / 5 / 6.25 kHz	5 / 6.25 kHz
Current Consumption	TX: 11 A (50 W, 45 W), 6 A (25 W) RX: 2.5 A, Standby: 200 mA	
Operating Temperature Range	–30° C to +60° C	
Frequency Stability	Better than ±2.5 ppm	
RF Input-Output Impedance	50 Ohms	
Dimension (W x H x D)	165 x 45 x 155 mm	
Weight (Approx.)	1.3 kg	
Receiver Specification: measured by TIA/EIA-603		
Sensitivity 12 dB SINAD	0.25 µV	
Adjacent Channel Selectivity	75 / 65 dB	73 / 65 dB
Intermodulation	73 dB / 70 dB	
Spurious and Image Rejection	90 dB	80 dB
Audio Output	Internal: 4 W @ 18 Ohms, 5% THD External: 12 W @ 4 Ohms, 5% THD	
Transmitter Specification: measured by TIA/EIA-603		
Output Power	10 / 5 / 1 W	10 / 5 / 1 W
Modulation	16K0F3E, 11K0F3E	
Maximum Deviation	± 5.0 kHz / ± 2.5 kHz	
Audio Distortion	< 3% @ 1kHz	
Spurious Emissions	70 dB below carrier	

Applicable MIL-STD

Standard	MIL 810C Methods/ Procedures	MIL 810D Methods/ Procedures	MIL 810E Methods/ Procedures	MIL 810F Methods/ Procedures
High Temperature	501.1/Procedure II	-	-	-
Low Temperature	502.1/Procedure I	-	-	-
Blowing Sand & Dust	-	-	510.3/Procedure I	-
Vibration	514.2/Procedure VIII, X	514.3/Procedure I Cat. 10	514.4/Procedure I Cat. 10	514.5/Procedure I Cat. 20, 24
Shock	516.2/Procedure I, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV, VI

Specifications are subject to change without notice or obligation.

VERTEX STANDARD is registered in the US Patent & Trademark Office. All other product or service names are the property of their respective owners. © Vertex Standard Co. Ltd. 2009 EXPSS2100/2200_05/2009