

Ultralow temperature freezer

DFU-V / DFUD-V (shelf-cooling type)
DFU-P / DFUD-P (Power Plus model)

Upright type Validity(Shelf Cooling Type) – (DFU-V / DFUD-V)

Product features and specifications

- Realization of strong cooling power with installment of copper pipes in each shelf and accurate and even temperature profile inside



Ultralow temperature freezer (Shelf cooling type Validity freezer)-Single door

Model	DFU-128V			DFU-256V			DFU-374V			DFU-446V			DFU-558V			DFU-657V			DFU-740V			DFU-868V		
Temperature range	AE	BE	CE	AE	BE	CE	AE	BE	CE	AE	BE	CE	AE	BE	CE	AE	BE	CE	AE	BE	CE	AE	BE	CE
-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	
External size	W710 x D750 x H1390	W710 x D750 x H1990	W860 x D800 x H1951	W860 x D900 x H1951	W1010 x D900 x H1901	W1010 x D990 x H1901	W1010 x D1010 x H2001	W1010 x D1010 x H2001	W1010 x D1151 x H2001	W450 x D475 x H600	W450 x D475 x H1200	W600 x D520 x H1200	W600 x D620 x H1200	W750 x D620 x H1200	W750 x D730 x H1200	W750 x D750 x H1300	W750 x D891 x H1300							
Internal size	128L	256L	347L	446L	558L	657L	731L	868L	Capacity necessary for installment AC220V 1ph (50/60Hz)															
Weight	210kg	300kg	370kg	380kg	400kg	420kg	450kg	500kg	Capacity necessary for installment AC220V 1ph (50/60Hz)															

Ultralow temperature freezer (Shelf cooling type Validity freezer)-Double door

Model	DFUD-374V			DFUD-446V			DFUD-558V			DFUD-657V			DFUD-740V			DFUD-1080V			DFUD-1215V			DFUD-1260V		
Temperature range	AE	BE	CE	AE	BE	CE	AE	BE	CE	AE	BE	CE	AE	BE	CE	AE	BE	CE	AE	BE	CE	AE	BE	CE
-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	
External size	W860 x D800 x H1951	W860 x D900 x H1951	W1010 x D900 x H1901	W1010 x D990 x H1901	W1010 x D1010 x H2001	W1460 x D1010 x H1990	W1610 x D1010 x H1990	W2260 x D1010 x H1583	W600 x D520 x H1200	W600 x D620 x H1200	W750 x D620 x H1200	W750 x D730 x H1200	W750 x D750 x H1300	W1200 x D750 x H1200	W1350 x D750 x H1200	W1400 x D750 x H1200	347L	446L	558L	657L	731L	1080L	1215L	1260L
Internal size	347L	446L	558L	657L	731L	1080L	1215L	1260L	Capacity necessary for installment AC220V 1ph (50/60Hz)															
Weight	380kg	390kg	410kg	425kg	455kg	500kg	520kg	540kg	Capacity necessary for installment AC220V 1ph (50/60Hz)															

Upright-Double door type Power plus model for Tropical climate

Product features and specifications

- The freezer appropriate for the surrounding temperature +40°C and over

Ultralow temperature freezer (Power Plus model-Double door Upright type)

Model	DFUD-374P			DFUD-446P			DFUD-558P			DFUD-657P			DFUD-740P			DFUD-1080P			DFUD-1215P			DFUD-1260P		
Temperature range	AE	BE	CE	AE	BE	CE	AE	BE	CE	AE	BE	CE	AE	BE	CE	AE	BE	CE	AE	BE	CE	AE	BE	CE
-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	-40°C	-55°C	-86°C	
External size	W860 x D800 x H1951	W860 x D900 x H1951	W1010 x D900 x H1901	W1010 x D990 x H1901	W1010 x D1010 x H2001	W1460 x D1010 x H1990	W1610 x D1010 x H1990	W2260 x D1010 x H1583	W600 x D520 x H1200	W600 x D620 x H1200	W750 x D620 x H1200	W750 x D730 x H1200	W750 x D750 x H1300	W1200 x D750 x H1200	W1350 x D750 x H1200	W1400 x D750 x H1200	347L	446L	558L	657L	731L	1080L	1215L	1260L
Internal size	347L	446L	558L	657L	731L	1080L	1215L	1260L	Capacity necessary for installment AC220V 1ph (50/60Hz)															
Weight	380kg	390kg	410kg	425kg	455kg	500kg	520kg	540kg	Capacity necessary for installment AC220V 1ph (50/60Hz)															

Control system

- Micro processor control system /Digital temperature indicator which adjust the temperature by 0.1°C
- Functions for setting double passwords to prevent access or control except administrators
- Data locking function

Alarm system and safety devices

- Alarm for filter cleaning period (Warm Condenser alarm)
- Alarm for high/low temperature of sight and auditory
- Equipped with pressure switch
- Equipped with overheating prevention switch
- Auto return system after blackout

Options Rack / Box / CO2 Backup system / LCD touch screen with SD card(or USB) - Basic -1channel (sensor 3channel, 6channel options) / U-system (remote alarm system and wireless control system – telecommunication subscription needed / Automatic voltage regulator / Cryogenic gloves / Battery backup (Control panel and alarm) / Recorder / VIP / *The minimum temperature of ultralow temperature freezer(C-type) is supplied with -91°C performance if the customer requests.