



**Ratings Range**

		<b>KV200U 60 Hz</b>	<b>KV220 50 Hz</b>
<b>Standby:</b>	<b>kW</b>	200	176
	<b>kVA</b>	250	220
<b>Prime:</b>	<b>kW</b>	182	160
	<b>kVA</b>	227	200



With Available Enclosure Accessory

**Standard Features**

- Kohler Co. provides one-source responsibility for the generating system and accessories.
- The generator set and its components are prototype-tested, factory-built, and production-tested.
- A one-year limited warranty covers all systems and components.
- Volvo engine with 24-volt battery charging alternator.
- Leroy Somer single-bearing alternator with insulation class H.
- Unit-mounted radiator with 50°C (122°F) ambient air capability.
- Skid and vibration isolators.
- Subbase fuel tank, 340 L (90 gal.).
- Dry type air filter.
- Main line circuit breaker.
- Microprocessor controller.
- Battery, battery rack, and cables.
- Industrial exhaust silencer (loose).
- Operation and installation literature.

**Generator Set Ratings**

Alternator	Voltage	Ph	Hz	Standby Rating		Prime Rating	
				kW/kVA	Amps	kW/kVA	Amps
	120/208	3	60	200/250	660	182/227	632
	127/220	3	60	200/250	656	182/227	598
	254/440	3	60	200/250	328	182/227	299
	277/480	3	60	200/250	300	182/227	274
	347/600	3	60	200/250	240	182/227	219
	115/200	3	50	176/220	635	160/200	578
LSA462M5	110/220	3	50	176/220	577	160/200	525
	127/220	3	50	176/220	577	160/200	525
	115/230	3	50	176/220	552	160/200	503
	120/240	3	50	176/220	529	160/200	482
	220/380	3	50	176/220	334	160/200	304
	230/400	3	50	176/220	318	160/200	289
	240/415	3	50	176/220	306	160/200	279

**RATINGS:** All three-phase units are rated at 0.8 power factor. See TIB-109 for generator set derate tables. Obtain the technical information bulletin (TIB-101) on ratings guidelines for the complete ratings definitions.  
**PRP:** Prime power is available for an unlimited number of annual operating hours in variable load applications in accordance with ISO-8528/1. A 10% overload capability is available for a period of 1 hour within a 12-hour period of operating in accordance with ISO-3046/1.  
**ESP:** The emergency standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO-8528/1. Overload is not allowed. The generator set manufacturer reserves the right to change the design or specifications without notice and without any obligation or liability whatsoever.

# Alternator Specifications

- NEMA-MG21, UTE NF C51.111, VDE 0530, BS 4999, CSA standards compliance for temperature rise and motor starting.
- Self-ventilated and dripproof construction.
- Vacuum-impregnated windings with fungus-resistant epoxy varnish for dependability and long life.
- Superior voltage waveform from a two-thirds pitch stator and skewed rotor.

Specifications	60 Hz	50 Hz
Ratings voltage	480	400
Standby rating @ 27°C, kVA		223
Prime rating @ 40°C, kVA		200
Efficiency @ full load		92.3%
Air flow, m <sup>3</sup> /min. (cfm)	25.8 (911)	
Direct axis subtransient reactance (X <sup>"d</sup> )	8.9%	

Specifications	Alternator
Manufacturer	Leroy Somer
Type	4-Pole, Rotating-Field
Exciter type	Shunt
Leads: quantity, type	12, Reconnectable
Voltage regulator	Solid State, R230
Insulation:	NEMA MG1
Material	Class H
Bearing: quantity, type	1, Sealed
Coupling	Direct
Voltage regulation, no-load to full-load	±1%

## Application Data

### Engine

Engine Specifications	60 Hz	50 Hz
Manufacturer	Volvo	
Engine model	TAD722GE	
Engine type	4-Cycle, Turbocharged, Aftercooled	
Cylinder arrangement	6 Inline	
Displacement, L (cu. in.)	7.15 (436)	
Bore and stroke, mm (in.)	108 x 130 (4.2 x 5.1)	
Compression ratio	18.1:1	
Piston speed, m/min. (ft./min.)	468 (1536)	390 (1278)
Rated rpm	1800	1500
Max. power at rated rpm, kWm (BHP)	268 (359)	242 (324)
Governor type	Isochronous	
Frequency regulation, no-load to full-load	ISO 5%	
Frequency regulation, steady state	±0.5%	
Air cleaner type, all models	Dry	

### Exhaust

Exhaust System	60 Hz	50 Hz
Exhaust manifold type	Dry	
Exhaust flow at rated kW, m <sup>3</sup> /min. (cfm)	41.1 (1451)	33.9 (1197)
Exhaust temperature at rated kW, dry exhaust, °C (°F)	494 (921)	540 (1004)
Maximum allowable back pressure, kPa (in. Hg)	9.7 (2.9)	
Exhaust outlet size at engine hookup, mm (in.)	—	

### Engine Electrical

Engine Electrical System	60 Hz	50 Hz
Battery charging alternator:	24 Volt	
Ground (negative/positive)	Negative	
Volts (DC)	24	
Starter motor rated voltage (DC)	24	
Battery, recommended cold cranking amps (CCA):	Two, —	
Quantity, CCA rating each	Two, —	
Battery voltage (DC)	24	

### Fuel

Fuel System	60 Hz	50 Hz
Max. fuel flow, Lph (gph)	450 (118.9)	360 (95.1)
Fuel prime pump	Manual	
Recommended fuel	#2 Diesel	
Fuel tank capacity, L (gal.)	390 (103)	

### Lubrication

Lubricating System	60 Hz	50 Hz
Type	Full Pressure	
Oil pan capacity, L (qt.)	31 (32.8)	
Oil pan capacity with filter, L (qt.)	34 (36)	

### Cooling

Radiator System	60 Hz	50 Hz
Ambient temperature, °C (°F)	50 (122)	
Radiator system capacity, including engine, L (gal.)	35.8 (9.46)	
Heat rejected to cooling water at rated kW, dry exhaust, kW (Btu/min.)	103 (5863)	91 (5179)
Water pump type	Centrifugal	
Fan, kWm (HP)	7.4 (9.9)	4.4 (5.9)
Max. restriction of cooling air, intake and discharge side of radiator, kPa (in. H <sub>2</sub> O)	0.15 (0.6)	

# Application Data

## Operation Requirements

Air Requirements	60 Hz	50 Hz
Radiator-cooled cooling air, m <sup>3</sup> /min. (scfm) *	—	—
Combustion air, m <sup>3</sup> /min. (cfm)	15.9 (561)	12.7 (447)
* Air density = 1.20 kg/m <sup>3</sup> (0.075 lbf/ft <sup>3</sup> )		

Fuel Consumption	60 Hz	50 Hz
<b>Diesel, Lph (gph) at % load</b>	<b>Standby Rating</b>	
110% (standby rating)	—	—
<b>Diesel, Lph (gph) at % load</b>	<b>Prime Rating</b>	
100% (of the prime rating)	50.5 (13.3)	44.3 (11.7)
75% (of the prime rating)	36.5 (9.6)	32.5 (8.6)
50% (of the prime rating)	24.5 (6.5)	21.8 (5.7)

## Controllers



### Decision-Maker™ 1000

#### Automation

- Test LEDs
- Voltage and speed stabilization

#### Engine Parameters

- Engine speed indication (with LCD message)
- Battery voltage indication (with LCD message)
- Elapsed hour meter (with LCD message)
- Fuel solenoid control
- Starter control

#### Measurements

- Frequency, Hz (with LCD message)

#### Operation and/or Safety Lights

- Oil pressure fault
- Water temperature fault
- Fail to start fault
- Overspeed fault ( $\geq 60$  kVA)
- Set ready for load
- Charging alternator fault
- General alarm
- General fault
- Panel lamp
- Emergency stop fault

#### Safety Devices

- Overspeed fault
- Automatic standby

#### Miscellaneous

- Fault reset
- Three-phase with or without neutral, two-phase, or single-phase use



### Decision-Maker™ 4000

#### Standard Features

- Large LCD display panel
- Unique control wheel for system access
- User buttons for start, stop, menu, and escape
- Emergency stop button
- On/off key switch
- Panel-mounted battery fuse
- Panel-mounted USB ports for PC access and software upgrades
- Password protected access to control parameters
- Upgradeable software for future enhancements

#### LCD Panel Features

- 600 x 800 resolution
- Multiple lines of text or graphic display
- Icons for quick identification of system status
- Five languages: English, French, German, Portuguese, and Spanish

#### Communication Features

- Engine communication via CANbus
- Modbus communication via RS-485 or Ethernet
- PC and flash drive connections via USB

#### Functions

- View and adjust system operation parameters
- View system faults

#### Viewable/Selectable Parameters (may require optional module)

- Voltage: phase-to-neutral, total voltage
- Current
- Frequency
- Power (active/reactive/apparent)
- Power factor
- Engine speed
- Oil pressure
- Coolant temperature
- Battery voltage
- Fuel level (%)
- Time delays

#### Viewable Faults (over 60 individual faults are monitored) including:

- Alternator protection
- Circuit breaker and ground fault protection
- Communication and engine ECM monitoring
- Cooling air monitoring
- Electrical charging system
- Engine cooling system
- Engine lube system
- Fuel system
- Generator set status

## Available Accessories

### Enclosed Unit

- Sound Enclosure M227, 60 Hz, 71.7 dB(A) @ 7 m (23 ft.), Standby (with enclosed critical silencer)
- Sound Enclosure M227, 50 Hz, 68.5 dB(A) @ 7 m (23 ft.), Standby (with enclosed critical silencer)

### Open Unit

- Exhaust Silencer, Critical 40 dB(A) Reduction
- Exhaust Silencer, Residential 29 dB(A) Reduction
- Flexible Exhaust Connector
- Protection Mesh for Exhaust Parts

### Cooling System

- Block Heater [recommended for ambient temperatures below 0°C (32°F)]
- Radiator Core Guard

### Decision-Maker™ 1000 Controller

- Alarm Horn
- Analog Indicator
- Differential Protection with Time and Sensitivity Adjustment
- Differential Triggering Fault
- External ATS Position
- External Starting Order
- Line Voltages, Volts Indicator
- Overload or Short-Circuit Fault
- Permanent Insulation Controller
- Phase Currents, Amps Indicator
- Plug Preheating
- Plug Preheating Control
- Remote Start Capability
- Single Voltages, Volts Indicator
- Utility Sensing, 3-Phase
- Water Preheating Control

### Decision-Maker™ 4000 Controller

- Alternator Protection
- Audible Alarm Module
- Five Expandable Modules with Four Inputs/Six Outputs Each
- Network Modules (RTC and GSM modems and ethernet router)
- NFPA-110 Module
- Remote Annunciator
- Voltage/Speed Adjustment Module
- WinTelys Software

### Fuel System

- Automatic Fuel Tank Fill Kit
- Subbase Fuel Tank with Secondary Containment Basin
- Subbase Fuel Tank Leak Alarm
- Water Separator Fuel Filter

### Electrical System

- Battery Charger, Equalize/Float Type
- Battery Isolator Switch

### Engine and Alternator

- Alternator Strip Heater
- Air Cleaner, Heavy Duty (with air restriction indicator)
- Droop Kit with 3-Function Voltage Regulator
- Lube Oil Drain Pump
- PMG Alternator and Voltage Regulator
- Tropical Heavy-Duty Alternator Insulation

### Miscellaneous Accessories

- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_


## Dimensions and Weights

### Open Model



Overall Size, L x W x H, mm (in.): 2370 x 1114 x 1480 (93 x 44 x 58)  
 Weight, wet, kg (lb.): 2200 (4850)

### With Available Enclosure Accessory



Overall Size, L x W x H, mm (in.): 4004 x 1380 x 2125 (158 x 54 x 84)  
 Weight, wet, kg (lb.): 3160 (6966)

NOTE: This drawing is provided for reference only and should not be used for planning installation. Contact your local distributor for more detailed information.

**DISTRIBUTED BY:**