



Traction motor data		
1	Type : Motor DC Permanent Magnet	
2	Power (S2 - 60 min)	W 500
3	Motor voltage	V 24
4		
5	Speed	Rpm 2800
6		
7	Current (500 W)	A 27
8	Torque (500 W)	Nm 1.7
9		
10		
11	Enclosure	IP 23
12	Brake torque	Nm 4
Gear data		
13	Max input motor power	W 500
14	Gear ratio	i 1:32.6
15	Max accel. and braking torque	Nm 230
16		
17	Wheel torque	Nm 42
18		
19		
20		
21	Lubrication	Grease
22	Max load on vulkollan wheel	Kg 660
23	Max load on poliurethan wheel	Kg 600
24	Max load on solid rubber wheel	Kg 420
Steering motor data		
25	Type : Motor DC	
26	Power (S2 - 60 min)	W
27	Motor voltage	V
28		
29	Speed	Rpm
30		
31	Current (W)	A
32	Motor torque (W)	Nm
33	Enclosure	IP
34		
35	Steering gear ratio	i
36	Efficiency of steering gear	η

Available on request	
A	Motors: Permanent Magnet, Series Wound, Sepex, AC
B	Voltages: 12V, 24V, 36V, 48V, 72V, 80V
C	Gear Ratio: 1:21, 1:26.6, 1:32.6
D	Encoders application
E	

Data : 17/10/2007	Scala : 1:3.5	A3
Date :	Scale :	
Dis : C.M.		
Drawn :		